

Shearwater Alloy RIB

Supertough RIB

All four models – the 260RIB, 280RIB, 310RIB and 340RIB – are designed for a larger payload.

The Shearwater has larger volume tubes, which are light and portable enough to deck stow, yet are built extra tough for the roughest conditions. Pressed hull strakes add to the strength as well as deflecting the wake for a drier ride. The 280RIB,

310RIB and 340RIB all feature fuel tank storage and triple air chambers. A centre transom support, keel capping, deck grip and davit lifting points are standard on all four models.

Features

- feathering oars
- removable floating seat
- foot pump
- service kit
- transom protection plate
- internal auto bailing drain
- davit lifting points
- instruction bulletin





Specifications

	Length		Beam		Tube Diameter		Weight		Air Chambers
	External	Internal	External	Internal	Fwd	Aft			
260RIB	2.6m 8'5"	1.77m 5'8"	1.59m 5'1"	0.75m 2'5 1/2"	0.36m 14"	0.40m 16"	30kg 66lbs		2
280RIB	2.79m 9'2"	1.97m 6'5"	1.60m 5'2"	0.76m 2'6"	0.36m 14"	0.41m 16 1/4"	35kg 77lbs		3
310RIB	3.09m 10'2"	2.17m 7'1"	1.61m 5'2 1/2"	0.76m 2'6"	0.36m 14"	0.42m 16 1/2"	38kg 84lbs		3
340RIB	3.39m 11'2"	2.47m 8'1"	1.61m 5'2 1/2"	0.76m 2'6"	0.36m 14"	0.42m 16 1/2"	45kg 99lbs		3

	Payload		Max hp/shaft	Height Overall	Hull degree deadrise	PackDown Sizes		
			short	0.70m 2'3"	12°	Length	Width	Height
260RIB	400kg 880lbs	5hp	short	0.70m 2'3"	12°	260RIB 2.04m 6'5"	1.0m 3'3"	0.42m 1'4 1/2"
280RIB	450kg 990lbs	10hp	short	0.70m 2'3"	12°	280RIB 2.24m 7'2"	1.0m 3'3"	0.42m 1'4 1/2"
310RIB	540kg 1188lbs	15hp	short	0.70m 2'3"	12°	310RIB 2.52m 8'3"	1.0m 3'3"	0.42m 1'4 1/2"
340RIB	620kg 1364lbs	18hp	short	0.70m 2'3"	12°	340RIB 2.84m 9'3"	1.0m 3'3"	0.42m 1'4 1/2"